




STIRLING^{TM/MC}

by/par Westbrook Systems



Model/Modèle: 48-084-TDD


G.V.W./PVT:	1980 lbs
Payload/Charge:	1580 lbs
Weight/Poids:	400 lbs
Int. Width/Largeur int.:	4'1" / 4 pi., 1 po.
Int. Length/Longueur int.:	7'3" to 10'11" / 7 pi., 3 po. à 10 pi., 11 po.
Front Gate/Porte avant:	Expandable - 22" / Extensible - 22 po.
Tailgate/Porte arrière:	Expandable - 22" / Extensible - 22 po.
Sides/Ridelles:	15" solid sides / 15 po. solide
Suspension:	2200 lb Torsion/ orsion 2200 lb
Wheel/Roue:	4.80 X 12 LRC
Tie-Down Points/Anneaux:	4 in-floor / 4 encastrés
Lighting/Lumières:	Fully Sealed / Lumière étanche
Coupler/Boule d'attelage:	1 7/8" / 1 7/8 po.
Hitch Height/Hauteur d'attelage:	15" / 15 po.



E.Z. Lube™



Extend - Extensible



Galvalume™



Contact us/Contactez-nous
866-857-1445
www.stirlingpowerproducts.com



Made in Canada
Fabriqué au Canada
P/N:503151