




STIRLING^{TM/MC}

by/par Westbrook Systems



Model/Modèle: 60-084-TDR

G.V.W./PVT:	1998 lbs.
Payload/Charge:	1508 lbs.
Weight/Poids:	490 lbs.
Int. Width/Largeur int.:	5' / 5 pi.
Int/ Length/Longueur int.:	7'3" to 9'1" / 7 pi., 3 po. à 9 pi., 1 po.
Front Gate/Porte avant:	Expandable - 22" / Extensible - 22 po.
Tailgate/Porte arrière:	3-Way Ramps / Porte à positions
Sides/Ridelles:	15" solid sides / 15 po. solide
Suspension:	1500 lbs. Spring / 21500 lbs.
Wheel/Roue:	5.30 X 12 LRC
Tie-Down Points/Anneaux:	4 in-floor / 4 encastrés
Lighting/Lumières:	Sealed / Scellés
Coupler/Boule d'attelage:	2" / 2 po.
Hitch Height/Hauteur d'attelage:	15" / 15 po.



E.Z. LubeTM



Folds-in / Se rabat



GalvalumeTM



Contact us/Contactez-nous
866-857-1445
www.stirlingpowerproducts.com



Made in Canada
Fabriqué au Canada
P/N: 503124